

**Amendments to the Claims:**

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) An image generation system comprising:
  - a memory which stores a program and data for image generating; and
  - at least one processor which is connected to the memory and performs processing for image generating,
  - the processor performing:
    - depth cueing for an object on condition that the object is positioned within a depth cueing area such that the color of the object being more distant from a viewpoint is made closer to a target color, ~~the depth cueing area only being set near a backward clipping plane of a viewing volume based on a position of the viewpoint being part of a viewing volume based on a position of the viewpoint and includes a backward clipping plane of the viewing volume;~~
    - varying an alpha ( $\alpha$ ) value of the object on condition that the object is positioned within the depth cueing area so that the object being more distant from the viewpoint becomes more transparent;
    - varying a depth cueing value for each vertex of the object based on a Z-value for each vertex of the object;
    - varying the alpha value for each vertex of the object based on the Z-value for each vertex of the object;
    - sorting objects within the depth cueing area so that the objects are drawn in succession starting from an object nearest to the viewpoint; and
    - drawing an image viewable from a virtual camera in an object space in drawing order determined by the sorting processing while performing hidden-surface erasing

based on a Z-buffer process for the objects within the depth cueing area.

2. (Previously Presented) The image generation system as defined in claim 1, the processor further performing:  
drawing a most distant background including a color different from the target color.

3-9. (Canceled)

10. (Currently Amended) An image generation system comprising:  
a memory which stores a program and data for image generating; and  
at least one processor which is connected to the memory and performs processing for image generating,  
the processor performing:  
varying an alpha ( $\alpha$ ) value of an object depending on the distance between the object and the viewpoint on condition that the object is positioned within a depth cueing area, the depth cueing area ~~only being set near a backward clipping plane of a viewing volume based on a position of the viewpoint~~ being part of a viewing volume based on a position of the viewpoint and includes a backward clipping plane of the viewing volume;  
sorting objects within the depth cueing area so that the objects are drawn in succession starting from an object nearest to the viewpoint; and  
drawing an image viewable from a virtual camera in an object space in drawing order determined by the sorting processing while performing hidden-surface erasing based on a Z-buffer process for the objects within the depth cueing area.

11. (Currently Amended) A computer readable information storage medium encoded with a computer program, the computer program comprising a processing routine for implementing:  
depth cueing for an object on condition that the object is positioned within a

depth cueing area such that the color of the object being more distant from a viewpoint is made closer to a target color, the depth cueing area ~~only being set near a backward clipping plane of a viewing volume based on a position of the viewpoint being part of a viewing volume based on a position of the viewpoint and includes a backward clipping plane of the viewing volume;~~

varying an alpha ( $\alpha$ ) value of the object on condition that the object is positioned within the depth cueing area so that the object being more distant from the viewpoint becomes more transparent;

varying a depth cueing value for each vertex of the object based on a Z-value for each vertex of the object;

varying the alpha value for each vertex of the object based on the Z-value for each vertex of the object;

sorting objects within the depth cueing area so that the objects are drawn in succession starting from an object nearest to the viewpoint; and

drawing an image viewable from a virtual camera in an object space in drawing order determined by the sorting processing while performing hidden-surface erasing based on a Z-buffer process for the objects within the depth cueing area.

12. (Currently Amended) The computer readable information storage medium as defined in claim 11, further comprising a processing routine for implementing:

drawing a most distant background including a color different from the target color.

13-19. (Canceled)

20. (Currently Amended) A computer readable information storage medium encoded with a computer program, the computer program comprising a processing routine for implementing:

varying an alpha ( $\alpha$ ) value of an object depending on the distance between the object and the viewpoint on condition that the object is positioned within a depth cueing area, ~~the depth cueing area only being set near a backward clipping plane of a viewing volume based on a position of the viewpoint~~ being part of a viewing volume based on a position of the viewpoint and includes a backward clipping plane of the viewing volume;

sorting objects within the depth cueing area so that the objects are drawn in succession starting from an object nearest to the viewpoint; and

drawing an image viewable from a virtual camera in an object space in drawing order determined by the sorting processing while performing hidden-surface erasing based on a Z-buffer process for the objects within the depth cueing area.

21. (Currently Amended) An image generation method comprising:

depth cueing for an object on condition that the object is positioned within a depth cueing area such that the color of the object being more distant from a viewpoint is made closer to a target color, ~~the depth cueing area only being set near a backward clipping plane of a viewing volume based on a position of the viewpoint~~ being part of a viewing volume based on a position of the viewpoint and includes a backward clipping plane of the viewing volume;

varying an alpha ( $\alpha$ ) value of the object on condition that the object is positioned within the depth cueing area so that the object being more distant from the viewpoint becomes more transparent;

varying a depth cueing value for each vertex of the object based on a Z-value for each vertex of the object;

varying the alpha value for each vertex of the object based on the Z-value for each vertex of the object;

sorting objects within the depth cueing area so that the objects are drawn in

succession starting from an object nearest to the viewpoint; and

drawing an image viewable from a virtual camera in an object space in drawing order determined by the sorting processing while performing hidden-surface erasing based on a Z-buffer process for the objects within the depth cueing area.

22. (Original) The image generation method as defined in claim 21, further comprising:

drawing a most distant background including a color different from the target color.

23-26. (Canceled)

27. (Currently Amended) An image generation method comprising:

varying an alpha ( $\alpha$ ) value of an object depending on the distance between the object and the viewpoint on condition that the object is positioned within a depth cueing area, ~~the depth cueing area only being set near a backward clipping plane of a viewing volume based on a position of the viewpoint being part of a viewing volume based on a position of~~ the viewpoint and includes a backward clipping plane of the viewing volume;

sorting objects within the depth cueing area so that the objects is drawn sequentially from an object nearest to the viewpoint; and

drawing an image viewable from virtual camera in an object space in drawing order determined by the sorting processing while performing hidden-surface erasing based on Z-buffer process for the objects within the depth cueing area.

28. (Currently Amended) The image generation system as defined in claim 1, wherein the processor performs processing so that the depth cueing value increases based on an increase in the Z-value, the depth cueing value being a parameter for determining the strength of the depth cueing effect.

29. (Currently Amended) The image generation system as defined in claim 10,

wherein the processor performs processing so that the depth cueing value increases based on an increase in the Z-value, the depth cueing value being a parameter for determining the strength of the depth cueing effect.

30. (Currently Amended) The ~~program~~computer readable information storage medium as defined in claim 11,

wherein the depth cueing value increases based on an increase in the Z-value, the depth cueing value being a parameter for determining the strength of the depth cueing effect.

31. (Currently Amended) The ~~program~~computer readable information storage medium as defined in claim 20,

wherein the depth cueing value increases based on an increase in the Z-value, the depth cueing value being a parameter for determining the strength of the depth cueing effect.

32. (Currently Amended) The image generation method as defined in claim 21, wherein the depth cueing value increases based on an increase in the Z-value, the depth cueing value being a parameter for determining the strength of the depth cueing effect.

33. (Currently Amended) The image generation method as defined in claim 27, wherein the depth cueing value increases based on an increase in the Z-value, the depth cueing value being a parameter for determining the strength of the depth cueing effect.